

Flash Demon



| | |
|--------|------------------|
| Length | 10 in. (25.5 cm) |
| Width | 6.3 in. (16 cm) |
| Height | 3.5 in. (9 cm) |
| Weight | 6.5 lb (2.9 kg) |
| Part# | AE308UU0003 |

- ▶ Solid aluminum, NEMA 4, waterproof housing
- ▶ Military-style, waterproof, external connections
- ▶ One encoder input; optional second encoder or 12VDC power supply input
- ▶ User selectable tension input - single ended, differential, or I2C digital communications
- ▶ Two, 4–20 mA / 0-5V analog inputs
- ▶ Sample rate varies with encoder speed from 1–20 samples/second
- ▶ Any size CompactFlash™ - 16MB to current market maximum size
- ▶ 5.75 in. (14.6 cm) x 2.5 in. (6.4 cm) real-time, backlit, 80 character display
- ▶ Intuitive menu structure navigated through a numeric keypad
- ▶ Four programmable depth alarms
- ▶ Non-volatile, internal, real-time clock
- ▶ Battery level indicator
- ▶ 6 volt, "D" cell (x4), power supply
- ▶ Display depth (x2), line speed, tension, plus two other analog sources
- ▶ Record all data to CompactFlash™ removable media cards
- ▶ Retrieve and store data on any computer with USB or CompactFlash™ capability
- ▶ View representations and merge data using customized Lee Specialties software

