

15K Hydraulic Grease Injector

Specifications & Dimensions

Specifications:

- **Working Pressure:** 17,500 psi max
- **Engine:** Four cylinder, 47 HP, water cooled, diesel engine with block heater and air shutoff valve
- **Pumps:**
 - Lee Specialties 15K intensifier pump
 - Grease pre-charge pump
 - Pneumatic grease pump for backup
 - Four single hand pumps
- **Split Grease Tank:** 75 US Gal (284 L)
- **Hydraulic Tank:** 53 US Gal (201 L)
- **Fuel Tank:** 22.5 US Gal (87 L)
- **Temp Rating:** -40°F to 250°F (-40°C to 121°C)
- **Hoses:**
 - 175 ft for grease supply and return
 - 175 ft hydraulic lines for packoff, linewiper, and head catcher
 - 125 ft hydraulic line for tool trap
 - 125 ft hydraulic lines for quad BOP

Dimensions:

- **Length:** 111 inches
- **Width:** 62 inches
- **Height:** 70 inches
- **Weight:** 2152 Kgs/4744 lbs.



The 15K Hydraulic Grease Injector is a diesel driven, hydraulically operated system containing Lee Specialties custom designed intensifier pump, live hydraulic swivels, high pressure reel swivels, and a high- pressure manifold demonstrating superior craftsmanship. This unit includes an accumulator system with four 5 US gal, nitrogen charged, bladder accumulator bottles.