

Assembly Part Number: AM693UU0007

Description: Hydraulic Cable Cutter 10k 3" Type O

Working Conditions		
Maximum Working Pressure		10,000 psi
Test Pressure		15,000 psi
Operating Temperature Range		-40°F / 250°F (-40°C / 121°C)
Elastomer Temperature Range		-40°F / 320°F (-40°C / 160°C)
Primary Service/Other Service		H2S/CO2
Design Specification		
Top Connection (Box)	Thread Size	5.75"
	TPI	4
	Seal Diameter	4.00"
Bottom Connection (Pin & Collar)	Thread Size	5.75"
	TPI	4
	Seal Diameter	4.00"
Hydraulic Connection		1/2" NPTF
Safety Shear Pin*		Shears at 650 psi
Elastomer Type		HNBR
Material		4130/4140
Dimensions		
Internal Diameter		3"
Overall Width		12.6"
Overall Length		24.96"
Made-Up Length		22.46"
Weight		105 lbs. (48 kg)
Design Criteria		
API 6A (Latest Edition)		Yes
NACE MR 0175 (Latest Edition)		Yes
Accessories		
Union C-Wrench		PM652UU1515-065A
Test Box		PM655UU0413
Test Pin		PM655UU0413
Seal Kit		AM680RK0075-6



Additional Information: Phosphate Coated, *safety shear pin ensures cable cutter will not function until at least a minimum required hydraulic pressure has been achieved.



All equipment renderings are included as a visual aid and may or may not be drawn to scale of the delivered product. Please refer to the engineered drawings provided with your equipment documentation for an accurate depiction of the physical properties and/or dimensions.