

Assembly Part Number: AM680WB0057

Description: Grease Head 10K 3" Type O 6 Section Single Point Injection

Working Conditions		
Maximum Working Pressure		10,000 psi
Test Pressure		15,000 psi
Operating Temperature Range		-40°F / 250°F (-40°C / 121°C)
Elastomer Temperature Range		-40°F / 320°F (-40°C / 160°C)
Primary Service/Other Service		H2S/CO2
Design Specification		
Top Connection (Box)	Thread Size	5.75"
	TPI	4
	Seal Diameter	4.00"
Bottom Connection (Pin & Collar)	Thread Size	5.75"
	TPI	4
	Seal Diameter	4.00"
Flow Tube ID		0.217" – 0.219"
Flow Tube Quantity		6
Grease Head Connections		LSI
Injection Port		1
Velocity Check		1
Elastomer Type		HNBR
Line Size		7/32"
Material		4130/4140
Dimensions		
Internal Diameter		0.500"
Overall Width		6.5"
Overall Length		100"
Made-Up Length		95"
Weight		178 lbs. (81 kg)
Design Criteria		
API 6A (Latest Edition)		Yes
NACE MR 0175 (Latest Edition)		Yes
Accessories		
Seal Kit		AM680RK0075-6



Additional Information: Phosphate Coated



All equipment renderings are included as a visual aid and may or may not be drawn to scale of the delivered product. Please refer to the engineered drawings provided with your equipment documentation for an accurate depiction of the physical properties and/or dimensions.