

Assembly Part Number: AM679UU0056-0219

Description: Linewiper Packoff 10k 3" Type O – 7/32" Line

Working Conditions		
Maximum Working Pressure		10,000 psi
Test Pressure		15,000 psi
Operating Temperature Range		-40°F / 250°F (-40°C / 121°C)
Elastomer Temperature Range		-40°F / 320°F (-40°C / 160°C)
Primary Service/Other Service		H2S/CO2
Design Specification		
Top Connection (Box)	Thread Size	N/A
	TPI	N/A
	Seal Diameter	N/A
Bottom Connection (Pin & Collar)	Thread Size	5.75"
	TPI	4
	Seal Diameter	4.00"
"Soft" 1-Piece Rubber		For stripping
"Hard" 2-Piece Rubber		For packing
Elastomer Type		HNBR
Dressed for		7/32"
Material		4130/4140
Dimensions		
Internal Diameter		3"
Overall Width		9"
Overall Length		36.1"
Made-Up Length		33.1"
Weight		105 lbs. (48 kg)
Design Criteria		
API 6A (Latest Edition)		Yes
NACE MR 0175 (Latest Edition)		Yes
Accessories		
Union C-Wrench		PM652UU1515-065A
Waste Return Hose		AM506UU0001
Seal Kit		AM679RK0056
Line Size Kit for 7/16" Line		
Upper Line Guide		PM679UU0014-0438
Bottom Line Guide		PM679UU0021-0438
Upper Line Guide Bushing		PM679UU0157-0438
1-Piece "Soft" Rubber		PM679UU0041-0438
2-Piece "Hard" Rubber		PM679UU0042-0438



Additional Information: Phosphate Coated



All equipment renderings are included as a visual aid and may or may not be drawn to scale of the delivered product. Please refer to the engineered drawings provided with your equipment documentation for an accurate depiction of the physical properties and/or dimensions.