

Assembly Part Number: AM661WB0098-0120

Description: Lubricator 10K 4" x 10' Type O Lightweight CRA

Working Conditions		
Maximum Working Pressure		10,000 psi
Test Pressure		15,000 psi
Operating Temperature Range		-40°F / 250°F (-40°C / 121°C)
Elastomer Temperature Range		-40°F / 320°F (-40°C / 160°C)
Primary Service/Other Service		H2S/CO2
Design Specification		
Top Connection (Box)	Thread Size	6.5"
	TPI	4
	Seal Diameter	4.75"
Bottom Connection (Pin & Collar)	Thread Size	6.5"
	TPI	4
	Seal Diameter	4.75"
Port Size, Type		N/A
Port Quantity		N/A
Construction		Threaded
Elastomer Type		HNBR
Material		Lightweight CRA
Dimensions		
Internal Diameter		4.06"
Overall Width		5"
Overall Length		124"
Made-Up Length		120"
Weight		287 lbs. (130 kg)
Design Criteria		
API 6A (Latest Edition)		Yes
NACE MR 0175 (Latest Edition)		Yes
Corrosion Resistant Alloy		Yes
Accessories		
Union C-Wrench		PM652UU1515-075A
Test Cap		AM660UU0036
Test Plug		PM660UU0044
Lubricator Lifting Clamp 5" OD		AM652UU0178
Seal Kit		AM661RK0098



Additional Information: Phosphate Coated



All equipment renderings are included as a visual aid and may or may not be drawn to scale of the delivered product. Please refer to the engineered drawings provided with your equipment documentation for an accurate depiction of the physical properties and/or dimensions.