

Assembly Part Number: AM675WB0009-0160

Description: Stuffing Box 10k 3" Type O - 0.160" Slickline

Working Conditions		
Maximum Working Pressure		10,000 psi
Test Pressure		15,000 psi
Operating Temperature Range		-40°F / 250°F (-40°C / 121°C)
Elastomer Temperature Range		-40°F / 320°F (-40°C / 160°C)
Primary Service/Other Service		H2S/CO2
Design Specification		
Top Connection (Box)	Thread Size	N/A
	TPI	N/A
	Seal Diameter	N/A
Bottom Connection (Pin & Collar)	Thread Size	5.75"
	TPI	4
	Seal Diameter	4.00"
Elastomer Type		HNBR
Dressed for		0.160" Slickline
Material		4130/4140
Dimensions		
Internal Diameter		3"
Overall Width		6.5"
Overall Length		20.1"
Made-Up Length		17.4"
Weight		42 lbs. (19 kg)
Design Criteria		
API 6A (Latest Edition)		Yes
NACE MR 0175 (Latest Edition)		Yes
Accessories		
Union C-Wrench		PM652UU1515-065A
Test Plug		PM655UU0260
Spacer		PM675UU0112
Seal Kit		AM675RK0009



Additional Information: Phosphate Coated



All equipment renderings are included as a visual aid and may or may not be drawn to scale of the delivered product. Please refer to the engineered drawings provided with your equipment documentation for an accurate depiction of the physical properties and/or dimensions.